



U.S. Department  
of Transportation

Research and  
Special Programs  
Administration

400 Seventh Street, S.W.  
Washington, D.C. 20590

JAN 18 2001

DOT-E 10823  
(THIRD REVISION)

EXPIRATION DATE: December 31, 2002

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Apical Industries, Inc.  
Oceanside, CA  
(Former Grantee: Q3 Comdyne Cylinders, Inc.)
2. PURPOSE AND LIMITATION:
  - a. This exemption authorizes the use of a FRP-1 type, non-DOT specification cylinder for the transportation in commerce of certain hazardous materials described in paragraph 6 subject to the limitations and special requirements specified here in. This exemption provides not relief from any Hazardous Materials Regulations (HMR) other than as specifically stated herein.
  - b. The safety analyses performed in development of this exemption only considered the hazardous and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.302(a)(1); § 173.304(a) and § 175.3 in that a non-DOT specification cylinder is not authorized, except as prescribed herein.
5. BASIS. This exemption is based on the application of Apical Industries, Inc. dated January 4, 2001, submitted in accordance with § 107.109.

JAN 18 2001

Continuation of DOT-E 10823 (3rd Rev.)

Page 2

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Proper shipping name/ Hazardous materials description	Hazard Class/ Division	Identi- fication Number	Packing Group
Compressed gas, n.o.s. (Oxygen enriched air, oxygen not over 39%)	2.2	UN1022	N/A
Argon, compressed	2.2	UN1006	N/A
Carbon dioxide, compressed	2.2	UN1013	N/A
Helium, compressed	2.2	UN1046	N/A
Hydrogen, compressed	2.1	UN1049	N/A
Methane, compressed or Natural gas, compressed (with high methane content)	2.1	UN1971	N/A
Neon, compressed	2.2	UN1065	N/A
Nitrogen, compressed	2.2	UN1066	N/A
Nitrous oxide	2.2	UN1070	N/A
Oxygen, compressed	2.1	UN1072	N/A

7. CONTROL MEASURES:

a. PACKAGING - Packaging prescribed is a non-DOT specification fiber reinforced plastic (FRP) full composite (FC) aluminum cylinder made in conformance with the following:

1. Comdyne I's design drawings # 11001000.AF dated 6-6-91, and #11001001.1F(A) dated 1-10-92, and the report of Design Qualification Tests P/N 11001000.AF, on file with the Office of Hazardous Materials Exemptions and Approvals (OHMEA); and

2. DOT FRP-1 Standard, Revision 2, dated February 15, 1987, (§ 178.AA) contained in Appendix A of this exemption, except as follows:

JAN 18 2001

Continuation of DOT-E 10823 (3rd Rev.)

Page 3

§ 178.AA-2 Type, size and service pressure.

Type 3FC cylinder consisting of resin impregnated continuous filament windings in helical and circumferential directions over a seamless aluminum liner made in compliance with § 178.AA-6; not over 100 pounds water capacity; and a service pressure of at least 900 psi but not greater than 3000 psi.

§ 178.AA-4 Duties of the Inspector.

(a) Verify conformance to the requirements in this exemption and to DOT FRP-1 Standard Revision 2, dated February 15, 1987.

(b) Verify conformance of aluminum liner with § 178.AA-6 below. Verify conformance of the filament and resin system components with the requirements specified in § 178.AA-5 below of this exemption.

(c) thru (g) \* \* \*.

§ 178.AA-5 Authorized Materials and Identification of materials.

(a) Aluminum liner must be 6061 alloy of T6 temper made from seamless drawn tubing.

(b) Filament material must be Kevlar 49™-8520 Denier, conforming to Aerospace Materials Specification AMS 3901. The filaments must be tested in accordance with ASTM-D2342-67 for strand strength and must have strand strength of 450,000 psi minimum.

For roving Denier determination, the filament material must be tested in accordance with ASTM D3317-74 and must be of at least 90% of the specified nominal value for the rovings. A manufacturer's certified test results for the rovings used in production may be used in lieu of testing.

(c) thru (e) \* \* \*

JAN 18 2001

Continuation of DOT-E 10823 (3rd Rev.)

Page 4

- b. Cylinders may not be used for underwater breathing purposes.
- c. Cylinders used in oxygen service must conform with § 173.302(a)(5)(i) through (a)(5)(iv).
- d. Cylinder service life may not exceed 15 years from the date of manufacture as marked on the cylinder.
- e. Each cylinder must be reinspected and hydrostatically retested every three years in accordance with § 173.34(e), as prescribed for DOT 3HT specification cylinders, except that the rejection elastic expansion does not apply and the permanent volumetric expansion may not exceed 5 percent of the total volumetric expansion at test pressure. Retest dates must be stamped on the exposed metallic surface of the cylinder neck or marked on a label securely affixed to the cylinder and overcoated with epoxy near the original test date. Reheat treatment or repair of rejected cylinders is not authorized. When a hydrostatic retest is repeated as provided for in § 173.34(e)(4)(v), only two such retests are permitted.
- f. No person may perform inspection and testing of cylinders subject to this exemption unless that person (1) has a current copy of this exemption at the location of such inspection and testing, and (2) complies with all the terms and conditions of this exemption regarding retesting. The marking of the retester's symbol on the cylinder certifies compliance with all of the terms and conditions of this exemption, which pertains to retesting.
- g. A cylinder that has been subjected to fire may not be returned to service.
- h. Transportation of flammable gases is not authorized aboard cargo vessel or aircraft.
- i. Cylinders must be packaged in accordance with § 173.301(k).
- j. Filling requirements are subject to all terms contained in § 173.302 for DOT 3AL specification cylinders.

JAN 18, 2001

8. SPECIAL PROVISIONS.

a. A person who is not a holder of this exemption who receives a package covered by this exemption may reoffer it for transportation provided no modification or change is made to the package or its contents and it is reoffered for transportation in conformance with this exemption and the HMR.

b. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

c. The cylinders described in this exemption are authorized only for normal transportation as an article of commerce i.e., the movement of hazardous materials packages from consignor to consignee.

d. New construction of cylinders after November 30, 2000, is not authorized.

e. The cylinders described in this exemption are authorized only for normal transportation as an article of commerce i.e., the movement of hazardous materials packages from consignor to consignee.

9. MODES OF TRANSPORTATION AUTHORIZED. Motor vehicle, cargo vessel, rail freight and cargo-aircraft only. (See paragraph 7(h) of this exemption.)

10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each motor vehicle, cargo vessel and aircraft used to transport packages covered by this exemption. The shipper must furnish a current copy of this exemption to the air carrier before or at the time the shipment is tendered.

11. COMPLIANCE. Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Hazardous materials transportation law, 49 U.S.C. 5101 et seq:

- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 171-180.
- o Registration required by § 107.601 et seq., when applicable.

JAN 18 2001

Continuation of DOT-E 10823 (3rd Rev.)

Page 6

Each "Hazmat employee", as defined in § 171.8 who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS. The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incidents involving the package and shipments made under the terms of this exemption.

Issued in Washington, D.C.:



for  
Robert A. McGuire  
Associate Administrator  
for Hazardous Materials Safety

JAN 18 2001

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.  
Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Copies of exemptions may be obtained from the AAHMS, U.S. Department of Transportation, 400 7th Street, SW, Washington, DC, 20590-0001, Attention: Records Center, 202-366-5046.

PO: sln